

# 4800

## Industrial 2D Area Imager



### Features

**Powered by Adaptus™ Imaging Technology 5.0** – Delivers extraordinary reading performance to enable ease-of-use and reader versatility.

**Aggressive, omni-directional point-and-shoot reading** of linear, PDF417, and full 2D matrix symbols to allow for greater throughput.

**NEW! Increased Resolution** – Improved image quality for vision-based applications.

**Rugged Packaging** – Impact absorbent, shock resistant housing withstands fifty 6.5 foot (2 meter) drops, and is sealed to resist dust, water, and contaminants from entering the unit. Backed by an industry leading 5-year warranty.

**NEW! Increased Motion Tolerance** – Greater stability in scanning; useful in fast-paced and mixed-symbology environments. Ease of use in all types of scanning applications; better hand/motion tolerance for linear codes.

**Future-Proof Technology** – The versatility of Adaptus Imaging Technology 5.0 serves broad image-based data capture needs; providing a solid solution for future application requirements.

**NEW! Faster Time to Read (TTR)** – Advanced Linear Decoding (ALD) is faster and reads more like a linear unit.

**NEW! Broader Depth of Field (DOF)** – Ability to read wider bar codes quickly and easily, including hard to read bar codes.

### Now Powered by New Adaptus™ Imaging Technology 5.0

The **4800 Industrial 2D Area Imager**, powered by Adaptus™ Imaging Technology 5.0, decodes faster, farther, and future-proofs your investment. This means employees spend less time trying to capture data, and more time creating a productive and cost effective work environment.

Whether the requirement is reading conventional linear bar codes or 2D matrix symbologies, the 4800 can capture them all today. If the application requires signature capture, OCR, or digital photography, the 4800 can do it. **The advanced imaging optics software in the 4800 quickly and easily determines the image content and transfers it to the host system.**

**The 4800 can be used in a wide range of applications** from circuit board manufacture to package delivery tracking. In addition, bar codes, images, and signature capture can provide positive proof of delivery. If discrepant material needs to be viewed by a production supplier, images can be captured and quickly transferred for immediate review and resolution, saving time and money.

The 4800 is extra tough. **Full shock-absorbing rubber protects the imager from dozens of 6.5 feet (2 meter) drops to concrete.** Since many application environments exhibit airborne dust and rain, the 4800 is sealed so these elements will not degrade performance. In addition to an IP54 enclosure specification, the 4800 is backed by an industry leading 5-year warranty.

For additional information, please contact your Hand Held Products representative, or visit [www.handheld.com](http://www.handheld.com).

# 4800 Specifications

## Performance

**Illumination LEDs:** 626nm ±30nm  
**Aiming:**  
**Green LED Aimer:** 526nm ±30nm  
**Image:** VGA, 752x480. Binary, TIFF, or JPEG output.  
**Working Range:**

	8.3 mil Linear (.021cm)	13 mil UPC (.033cm)	6.6 mil PDF417 (.017cm)	10 mil PDF417 (.025cm)	15 mil PDF417 (.038cm)	35 mil MaxiCode (.089cm)
<b>4800SR</b>						
<b>Near</b>	3.0 in. (7.6cm)	1.6 in. (4.1cm)	4.0 in. (10.2cm)	2.6 in. (6.6cm)	1.8 in. (4.6cm)	1.5 in. (3.8cm)
<b>Far</b>	7.1 in. (18.0cm)	12.7 in. (32.3cm)	5.7 in. (14.5cm)	8.5 in. (21.6cm)	9.7 in. (24.6cm)	12.5 in. (31.8cm)
<b>4800SF</b>						
<b>Near</b>	2.0 in. (5.1cm)	1.5 in. (3.8cm)	2.3 in. (5.8cm)	1.7 in. (4.3cm)	1.3 in. (3.3cm)	1.7 in. (4.3 cm)
<b>Far</b>	6.0 in. (15.2cm)	8.4 in. (21.3cm)	5.5 in. (14.0cm)	7.1 in. (18.0cm)	7.0 in. (17.8cm)	6.7 in. (17.0cm)

**Skew Angle:** ±40°  
**Pitch Angle:** ±40°  
**Motion Tolerance:** 4 in. (10 cm) per second

## Mechanical/Electrical

### Dimensions

**Length:** 5.3 in. (13.5 cm)  
**Height:** 6.4 in. (16.3 cm)  
**Width:** 3.2 in. (8.1 cm)  
**Weight:** 7.5 oz. (213 g)

**Housing:** UL 94V0 grade  
**Power Requirements:** 4.0 - 14Vdc at imager

**Current Draw (Typical):**

Input	Scanning	Idle
5 V	382mA	53mA

### Power Supply

**Noise Rejection:** Maximum 100mV peak to peak, 10 to 100 kHz

## Environmental

### Temperature

**Operating:** 14°F to +122°F (-10°C to +50°C)  
**Storage:** -40°F to 158°F (-40°C to +70°C)

**Humidity:** 0 to 95%, non-condensing

**Sealing:** IP54 (water and dust resistant)

**Mechanical Shock:** Operational after 50 drops from 6.5 ft. (2 m) to concrete

**Ambient Light:** 0 to 100,000 lux (full sunlight)

**ESD Protection:** Functional after 100 discharges at 15kV

**Vibration:** Withstands 5G peak from 22 to 300 Hz

**Agency:** FCC Class B, CE EMC Class B, CE Low Voltage Directive, IEC60825-1 LED Safety: Class 1, UL, cUL listed, TÜV, 2005 Sunrise Compliant  
**MTBF:** per MIL-HDBK-217F Ground Benign exceeds 82,000 hours

## Symbologies

**2 Dimensional:** PDF417, MicroPDF417, MaxiCode, Data Matrix, QR Code, Aztec, Aztec Mesas, Code 49, and EAN•UCC Composite.  
**Linear:** Codabar, Code 39 including PARAF, Interleaved 2 of 5, Code 2 of 5, Code 11, Code 93, Code 128, UPC, EAN/JAN, RSS.  
**Postal (SR/SF Only):** Postnet, Planet Code, British Post, China Post, Canadian Post, Japanese Post, KIX (Netherlands) Post  
**OCR Fonts (SR/SF Only):** OCR-A, OCR-B  
**Interfaces:** All popular PCs and terminals via keyboard wedge, keyboard replacement/direct connect, TTL level RS-232, TTL level Serial Wedge, USB, wand emulation (primary interface only), HHLC non-decoded laser compatible, True RS-232, IBM 468x, and IBM469x.  
**Warranty:** 5 year warranty

## Worldwide Offices

**Offices Serving North America**  
 Skaneateles Falls, NY  
 Tel: +1 315 685 8945  
 or, in North America: +1 800 582 4263  
 napresales@handheld.com  
 Charlotte, NC  
 Tel: +1 704 998 3998  
 or, in North America: +1 800 582 4263  
 napresales@handheld.com

**Offices Serving Europe, Middle East, and Africa**  
 Europe  
 Tel: +31 (0) 40 29 01 600  
 eupresales@handheld.com  
 United Kingdom  
 Tel: +44 (0) 1 925 240055  
 eupresales@handheld.com  
 Italy  
 Tel: +39 (0) 2 67 100752  
 eupresales@handheld.com

**France**  
 Tel: +33 (0) 1 41 158220  
 eupresales@handheld.com  
 Germany  
 Tel: +49 (0) 7 477 151377  
 eupresales@handheld.com  
 Spain  
 Tel: +34 93 228 78 68  
 eupresales@handheld.com

**Offices Serving Asia and the Pacific Rim**  
 Hong Kong  
 Tel: +852 2511 3050  
 appresales@handheld.com  
 Japan  
 Tel: +813 5770 6312  
 appresales@handheld.com  
 Shanghai  
 Tel: +86 21 6361 3818  
 appresales@handheld.com

**Offices Serving Latin America**  
 Naples, Florida  
 Tel: +1 239 263 7600  
 lapresales@handheld.com  
 São Paulo  
 Tel: +55 11 2178 0500  
 lapresales@handheld.com  
 Rio De Janeiro  
 Tel: +55 21 2178 0500  
 lapresales@handheld.com  
 Mexico  
 Tel: +52 55 5203 2100  
 lapresales@handheld.com

Web Site Address [www.handheld.com](http://www.handheld.com)

Hand Held Products, Inc., ("Hand Held Products") © 1999-2006. All rights reserved. Printed in the U.S.A.  
 Due to Hand Held Products' continuing product improvement programs, specifications and features herein are subject to change without notice.